elumatec

a voilàp company

AF 222

END-MILLING MACHINES



- For machining transoms and door profiles made of aluminium or plastic
- Manual feed of the routing unit
- Large cutting range of up to 400 mm
- Continuously adjustable table height
- Tool diameters of up to 280 mm can be used
- The material stop can be pivoted up to 60° to the left and right. Notching up to 30° (acute angles, left and right). Detent at 90° with index pin.
- Two installation positions for the material stop
- With quick tool change system and "Spindle Lock" for easy tool changing
- Precise, smooth-action and low-wear recirculating ball guides
- Horizontal and vertical pneumatic material clamping provides flexibility
- Depth stop for four different notching depths
- Integrated connecting piece with extractor hose for connection to an extraction system
- Pulsed coolant system
- Automatic safety curtain

Options

- Extraction system
- 4-fold turret stop for table height
- Digital display
- Cutting tools
- High performance cutting fluid

elumatec AG
Pinacher Straße, 61
75417 Mühlacker
Germany

Tel +49 7041-14-184
sales@elumatec.com
www.elumatec.com

The right to make technical alterations is reserved.


elumatec AG
Pinacher Straße, 61
75417 Mühlacker
Germany

Tel +49 7041-14-184
sales@elumatec.com
www.elumatec.com


The right to make technical alterations is reserved.



End milling machine AF 222/02



End milling machine AF 222/02



End milling machine AF 222/02

elumatec AG
Pinacher Straße, 61
75417 Mühlacker
Germany

Tel +49 7041-14-184
sales@elumatec.com
www.elumatec.com

The right to make technical alterations is reserved.