

28/08/2025



- Notching for cross-bars in curtain wall manufacturing
- Precise and safe notching is ensured because the workpiece is fixed and only the saw units move
- The cutting depth is set using an analogue display
- Manual adjustment of 550mm saw blade cutting angles with digital angle display
- Horizontal and vertical profile clamping
- 2-hand operation for sawing cycle

Options

- Saw blades
- High performance cutting fluid



elumatec AG Pinacher Straße, 61 75417 Mühlacker Germany Tel +49 7041-14-184 sales@elumatec.com www.elumatec.com The right to make technical alterations is reserved.

elumatec

TECHNICAL SHEET





Notching saw AKS V-550



Notching saw AKS V-550



Notching saw AKS V-550



elumatec AG Pinacher Straße, 61 75417 Mühlacker Germany Tel +49 7041-14-184 sales@elumatec.com www.elumatec.com The right to make technical alterations is reserved.



AKS V-550 / NOTCHING SAWS

Saw unit for notch cuts fixed at 0°:

- Saw blade diameter 350 mm
- Power output 2 kW with motor brake
- Saw blade speed 2,800 rpm

Saw unit for notch cuts $90^{\circ}+45^{\circ}$ and $90^{\circ}-20^{\circ}$:

- Saw blade diameter 550 mm
- Power output 3 kW with motor brake
- Saw blade speed 2,800 rpm
- Maximum notch size: 210 mm x 100 mm
- Compressed air supply 7 bar
- Weight 480 kg



elumatec AG Pinacher Straße, 61 75417 Mühlacker Germany Tel +49 7041-14-184 sales@elumatec.com www.elumatec.com The right to make technical alterations is reserved.