

## **TECHNICAL SHEET**

20/04/2024



Profile trolley for vertical storage and transportation of profiles

- Stable steel construction
- Vertical profile transportation
- Profile trolley with loading on one side
- Easy loading and unloading
- Sufficient for 60 80 profile bars
- Compartment dividers height is adjustable
- Supporting surface with bar grid floor
- Four castors, two of which have a fixing brake

#### **Options**

Plastic protector for PWS 2000

# **elumatec**

## **TECHNICAL SHEET**

20/04/2024




Profile transport trolley PWS 2000



**Casters** 

Four casters, two of which have a fixing brake, provide a high degree of mobility and easy, safe handling



**Compartment dividers** 

Compartment divider height is adjustable, Compartment width 100 mm, Compartment depth 540 mm



Easy loading and unloading

Profile trolley with loading on one side



Supporting surface

Supporting surface with bar grid floor



# Plastic protector for PWS 2000

All supporting surfaces have a non-slip PVC cladding which protects surfaces from damage during storage



Tel +49 7041-14 0 Fax: +49 7041-14 280 mail@elumatec.com www.elumatec.com The right to make technical alterations is reserved.



## **TECHNICAL SHEET**

20/04/2024

#### PWS 2000 / PROFILE TRANSPORT TROLLEYS

- Length 2,230 mm
- Width 800 mm
- Height 1,360 mm
- Two compartment dividers
- 18 compartments
- Roller diameter 125 mm
- Compartment width 100 mm
- Compartment depth 540 mm
- Unit height 1,150 mm
- Weight 105 kg
- Load 350 kg