

11/12/2025

SBZ**122/73**

Machining centres



- Designed for economical and efficient machining of aluminium, PVC and thin-walled steel profiles
- All operations, such as routing, drilling and tapping, are performed while the profile bar is stationary to protect the profile surfaces
- A-axis continuously adjustable from -120° to +120°
- Clamp positioning automatic
- Better machining results thanks to the intelligent control technology
- Fast positioning of the machining unit with up to 120 m/min thanks to dynamic servo drives
- Tapping without compensation chuck
- Automatic tool changer with twelve tool tray positions (without tools)
- State-of-the-art 4-axis controller
- Ergonomic operation thanks to the advanced inclined bed
- The absolute rotary encoder system means no main axis homing is required
- Automatic clamp recognition and positioning prevents collisions
- · Power torque routing motor with enclosed speed control for short spindle start-up and braking times.
- Certified, drive-integrated safety functions
- Low power consumption thanks to the intelligent control technology
- DC link coupling in the axis drives for greater energy efficiency
- Uninterruptible power supply (UPS)
- Windows operating system
- 18.5" panel PC, i5 processor, USB ports and network connection
- · Simple, stress-free program entry with eluCam on the operating panel, even during operation
- Remote online maintenance

Machine configuration

- Water-cooled 7 kW, S1 routing spindle
- Enclosure to protect the operator
- Four horizontal, pneumatic material clamping units
- A material stop on the left
- Tool holder HSK-F63
- Swarf trays for swarf removal
- Minimum-volume lubrication system
- High performance cutting fluid
- Hand-held operator terminal
- Depth gauge

elumatec AG Pinacher Straße, 61 75417 Mühlacker Germany

Tel +49 7041-14-184 sales@elumatec.com

The right to make technical alterations is reserved.

1

elumatec

TECHNICAL SHEET

11/12/2025

Options

- Tools
- Tool holders
- Additional stop for overlength machining (left)
- Material reference stop (right) for positioning workpieces with overlength machining and second clamping disc
- Green Line cooling unit for the control cabinet with reduced energy consumption
- Barcode scanner
- Protective enclosure can optionally completely enclose the machine on all sides, with additional sound insulation
- Four clamps as standard. Can be equipped with up to eight clamps
- Double clamping and other accessories on request
- 21.6" panel PC, i7 processor
- Note holder
- Sound insulation hood
- Clamping unit optimised to prevent collisions
- Wireless measurement sensor



11/12/2025



A-axis angle adjustment

Continuously adjustable angle setting from - 120° to $+120^{\circ}$



Profile machining centre SBZ 122/73

Inclined bed




Tool magazine

The tool magazine with 12-fold tool changer allows quick, easy setup and minimal secondary time




Profile machining centre SBZ 122/73

Double clamping unit



Machining area, Y and Z-axes

Profile machining from above



Machining area, Y and Z-axes

Profile machining from above and from




Tel +49 7041-14-184 sales@elumatec.com www.elumatec.com The right to make technical alterations is reserved.





11/12/2025



Machining area, Y and Z-axes

Profile machining from the front and from behind



11/12/2025

SBZ 122/73 / MACHINING CENTRES

SBZ 122/73

Max. machining length without profile end machining 4,050 mm

Max. machining length with profile end machining

Traverse path X-axis
4,176 mm, Vmax. 120 m/min.
Traverse path Y-axis
1,040 mm, Vmax. 60 m/min.
Traverse path Z-axis
540 mm, Vmax. 30 m/min.
Direction of machining
Positioning accuracy
+/- 0.1 mm

Routing spindle speed max. 20,000 rpm
Routing spindle power 7 kW, S1 (water-cooled)

Tool holder HSK-F63
Tool changing automatic
Tool tray positions in the automatic magazine 12

Angle head No
Disc milling cutter diameter 120 mm

Saw blade diameter - 120 m

Tool length (from extent of taper) max. 150 mm

Clamp positioning automatic
Clamps Basic (with linear guides)

Software eluCam

Compressed air supply > 7 bar Power supply $400 \text{ V}, 3\sim, 50 \text{ Hz}, 25 \text{ A}$ Air consumption per minute approx. 185 I with spraying

Total length 7,643 mm

Depth 2,171 mm

Height 3,000 mm

Weight approx. 3,800 kg

elumatec AG Pinacher Straße, 61 75417 Mühlacker Germany Tel +49 7041-14-184 sales@elumatec.com www.elumatec.com The right to make technical alterations is reserved.