

28/08/2025

TS**161/21** 



TABLE SAWS

- $^{\bullet}$  Accuracy is achieved by cutting from below for 90° saw cuts and angled cuts
- $^{\circ}\,$  Wide pivoting range of up to 45° to the left and 0° to the right
- The special pivoting mechanism with integrated turn table enables working from the front at any angle setting
- The back fence is adjustable to allow optimal use of the saw blade capacity for wide and flat profiles
- Manual saw feed
- Equipped with saw blade and machine base as standard
- Pneumatic material clamping (vertical)
- Pulsed coolant system
- Maintenance unit

### Options

- Digital display for pivoting angles
- Extraction system
- Length stop and measuring systems
- Roller conveyors
- High performance cutting fluid



elumatec AG Pinacher Straße, 61 75417 Mühlacker Germany Tel +49 7041-14-184 sales@elumatec.com www.elumatec.com The right to make technical alterations is reserved.

# elumatec

Table saw TS 161/21



Table saw TS 161/21 + MMS 200



**TECHNICAL SHEET** 

Table saw TS 161/21




Table saw TS 161/21




Table saw TS 161/21Cutting diagram TS 161/21



elumatec AG Pinacher Straße, 61 75417 Mühlacker Germany Tel +49 7041-14-184 sales@elumatec.com www.elumatec.com The right to make technical alterations is reserved.



## **TS 161/21** / TABLE SAWS

- For cutting range, see cutting diagram
- Saw blade diameter 280 mm
- Saw blade speed 3,200 rpm
- $^{\bullet}$  Power supply 230/400 V, 3~, 50 Hz
- Power output 1.05 kW
- Length 650 mm, depth 750 mm, height 1,300 mm, weight 130 kg



elumatec AG Pinacher Straße, 61 75417 Mühlacker Germany Tel +49 7041-14-184 sales@elumatec.com www.elumatec.com The right to make technical alterations is reserved.