


18/09/2025



Trolley for transporting and providing a sorted selection of cut-to-length reinforcement profiles • Stable steel construction

- Vertical storage and transportation of steel profiles
- Compact outside dimensions
- Well-organised arrangement of fixed-length profiles
- Four castors, two of which have a fixing brake




elumatec AG Pinacher Straße, 61 75417 Mühlacker Germany Tel +49 7041-14-184 sales@elumatec.com www.elumatec.com The right to make technical alterations is reserved.

elumatec


TECHNICAL SHEET

18/09/2025

Reinforcement trolley AW 800



Compartments Six compartments, compartment size 190 x 265 mm



Grid frame Two grid frames with height adjustment



Casters

Four casters, two of which have a fixing brake, provide a high degree of mobility and easy, safe handling



elumatec AG Pinacher Straße, 61 75417 Mühlacker Germany Tel +49 7041-14-184 sales@elumatec.com www.elumatec.com The right to make technical alterations is reserved.



- Length 800 mm
- Width 600 mm
- Height 960 mm
- Six compartments
- Weight 35 kg
- Load 400 kg
- Roller diameter 125 mm



elumatec AG Pinacher Straße, 61 75417 Mühlacker Germany Tel +49 7041-14-184 sales@elumatec.com www.elumatec.com The right to make technical alterations is reserved.