TECHNICAL SHEET

15/07/2025



Commissioning trolley for in-house transportation of window elements

- Stable steel construction
- For in-house transportation
- Profile supports with rubber surface
- Four castors, two of which have a fixing brake



Pinacher Straße, 61 75417 Mühlacker Germany Tel +49 7041-14-184 sales@elumatec.com www.elumatec.com The right to make technical alterations is reserved.



TECHNICAL SHEET

nage not found of type unknown

Commissioning trolley KW 1



Casters

Four casters, two of which have a fixing brake, provide a high degree of mobility and easy, safe handling



Supports with rubber strip

Supporting surfaces equipped with rubber strips to protect profiles from damage



Transport handles Transport handle on both sides for mobility



Pinacher Straße, 61 75417 Mühlacker Germany Tel +49 7041-14-184 sales@elumatec.com www.elumatec.com The right to make technical alterations is reserved.



KW 1 / COMMISSIONING TROLLEYS

- Length 1,690 mm
- Width 910 mm
- Height 1,768 mm
- Weight 100 kg
- Load 400 kg
- Roller diameter 125 mm



p**elumatec AG** Pinacher Straße, 61 75417 Mühlacker Germany Tel +49 7041-14-184 sales@elumatec.com www.elumatec.com The right to make technical alterations is reserved.

15/07/2025