


05/12/2025

## **VE3000**

Inspection and glazing unit



Inspection and glazing unit for glazing and final inspection in individual and serial assembly line production

- Stable steel construction
- Quick and precise assembly of windows, doors and elements
- Precision ensured through parallel clamping bar pressing technique
- For glazing and functional checks
- For connecting frames and sashes
- Height continuously adjustable
- Two pressing bars which fold down and can be moved pneumatically
- Easy operation by means of foot switch
- 4-fold compressed air supply

### **Options**

- Lead-in rollers, cmpl., right
- Lead-in rollers, cmpl., left
- Profile protectors for support rollers
- Tilt adjustment of 0° 8°

elumatec AG Pinacher Straße, 61 75417 Mühlacker Germany Tel +49 7041-14-184 sales@elumatec.com www.elumatec.com The right to make technical alterations is reserved.

1



05/12/2025




Inspection and glazing unit VE 3000




Back support

Rear back support with plastic slide bars



**Supports** 

Lower roller conveyor with support rollers, L = 200 mm



### Foot switch

All functions are controlled via foot valves



### **Pressing bar**

Simultaneous, synchronous folding down and moving of the pressing bars ensure a minimum of time is required for opening and closing the press. Allows free passthrough of the window.



# Lead-in rollers, cmpl., right

Protective rollers for beginning or end of roller conveyor



Tel +49 7041-14-184 sales@elumatec.com www.elumatec.com The right to make technical alterations is reserved.




05/12/2025



Lead-in rollers, cmpl., left

Protective rollers for beginning or end of roller conveyor



Tilt adjustment of 0° - 8°

Pneumatic tilt adjustment of 0° - 8°



**Profile protectors** 

Profile protectors for support rollers 200 (Alum./21 x). Support rollers covered with protective tubing for aluminium elements.



### **Mobility unit**

Mobility unit for KT/KTH/MS/VE. Mobility unit with flanged rollers and fixing brake



### Rails

Rails, 2.0 m, left and right



Tel +49 7041-14-184 sales@elumatec.com www.elumatec.com The right to make technical alterations is reserved.



05/12/2025

### VE 3000 / INSPECTION AND GLAZING UNIT

- Length 4,410 mm
- Width 1,180 mm
- Height 2,600 mm
- Max. clamping width 3,000 mm
- Min. clamping width 400 mm
- Height adjustment 500 mm
- Clamping bar height 2,300 mm
- Clamping bar width 120 mm
- Lower roller conveyor width 200 mm
- Weight 470 kg
- Load 200 kg
- Compressed air supply 7 bar
- Air consumption 35 l/min.