

17/09/2025



# VERTICAL ROLLER CONVEYORS



Vertical roller conveyor for transportation and storage of window elements

- Stable steel construction
- Expandable using modular system design
- Vertical roller conveyor for smooth transportation and storage of window elements
- Easy handling of window elements
- Every roller conveyor unit is 3,000 mm long
- Roller conveyor divided into three parts
- Plastic slide bars top and bottom
- Three mini-roller conveyors with rubber rollers, diameter 50 mm
- Basic unit without end rack

#### **Options**

- End rack for VR 2003/3003/4003
- End stop for VR
- Lead-in roller for VR
- Profile protectors for support rollers (Alum.)

elumatec AG Pinacher Straße, 61 75417 Mühlacker Germany Tel +49 7041-14-184 sales@elumatec.com

The right to make technical alterations is reserved.


1



17/09/2025



Vertical roller conveyor VR 3003




**Support rollers** 

Rollers throughout, Roller conveyor divided into three parts, 3x 120 mm. Roller conveyor units, 2,000 mm, 3,000 mm and 4,000 mm long



Mini-roller conveyor

Three mini-roller conveyors with rubber rollers, diameter 50 mm




**Back support** 

Rear back support with plastic slide bars, top and bottom



## Roller conveyor height adjustment

Lower roller conveyor height can be adjusted by means of adjustable feet



#### **Profile protectors**

Profile protectors for support rollers 3x 120 mm (Alum./33 x and Alum./48 x). Support rollers covered with protective tubing



Tel +49 7041-14-184 sales@elumatec.com www.elumatec.com The right to make technical alterations is reserved.



17/09/2025




Mini-roller conveyor height adjustment

Mini-roller conveyor height is adjustable



**End rack** 

End rack is mandatory at end of line




**End stop** 

End stop Rb = 3x 120 mm



#### Lead-in rollers

Protective rollers for beginning or end of roller conveyor L = 500 mm (pair) L = 250 mmmm (pair)



### Additional mini-roller conveyors

Additional mini-roller conveyors with rubber rollers top/bottom



Pinacher Straße, 61 75417 Mühlacker

Tel +49 7041-14-184 sales@elumatec.com www.elumatec.com

The right to make technical alterations is reserved.



17/09/2025

#### VR 3003 / VERTICAL ROLLER CONVEYORS

- Length 3,000 mm
- Width 900 mm
- Height 2,400 mm
- Support rollers divided into three parts 3 x 120 mm
- Unit height 2,100 mm
- Load 200 kg
- Weight 120 kg