



DG79

双头斜锯



- 坚固的铸件构造加上集成的圆工作台，保障稳固的型材支承和锯切
- 锯头切割摆动角度从0度到45度向左、向右不分级可调可进行外、内测量值的切割样式
- 垂直及水平气动夹具保证型材的最优化固定
- 标配锯片
- 标配E111数字显示器
- 计量冷却液装置

标准可选切割长度有

- 3,000 mm
- 4,500 mm
- 6,000 mm

选件

- 工件支架
- 中挺定位器
- 抽吸装置
- 材料夹紧装置
- 滚道
- 锯片
- 高效切割冷却液


控制方式

- 手动调节切割长度，配置数显定位装置 E 111
- 定位控制系统 E 390




双头斜榫切割机DG 79

DG 79 + E 111




双头斜榫切割机DG 79




双头斜榫切割机DG 79



双头斜榫切割机DG 79



双头斜榫切割机DG 79



双头斜榫切割机DG 79

切割图DG 79





DG 79 / □□□□

- 90° □□□□□□□□ 520 mm
- □□45 ° □□□□□□□□ 520 mm
- □□□□15° □□30° □□45° □□
- □□□□0 □□45 □□□□
- □□□□80 □□m
- □□□□2,800 □□□□
- □□ 230/400 V □□3~ □□50 Hz
- □□□□□□□□3 kW
- □□□□7 □□

